

	ColorMatcher Luminaire 425	ColorMatcher Light booth 2028	ColorMatcher Light booth 2540	ColorMatcher Light booth 3052	Tru-Vue 2	Tru-Vue 4	Tru-Vue 4D
Light sources	4	5	5	5	4	5	4
Dimming for Daylight, Store & Home-Light included							✓
Optional: Dimming for Daylight, Store & Home-Light	✓	✓	✓	✓			
Push Button Control	✓	✓	✓	✓		✓	✓
Rocker Switch Lamp Selectors					✓		
Auto Light Source Sequencing	✓	✓	✓	✓		✓	✓
Lamp timer for all sources	✓	✓	✓	✓			
Lamp timer only for primary light source					✓	✓	✓
Optically neutral diffuser	✓	✓	✓	✓			
Optional: Optically neutral diffuser					✓	✓	✓
Munsell N5 grey surround		220V models	220V models	220V models	220V models	220V models	220V models
Munsell N7 grey surround		120V models	120V models	120V models	120V models	120V models	120V models
Optional: N7 grey surround in place of N5 or N5 in place of N7		✓	✓	✓	✓	✓	✓
Optional: 45° viewing table		✓	✓	✓	✓	✓	✓
Optional: height adjustable floor stand		✓	✓	✓			
Standard Light Sources 120V models: D65, CWF, A, TL83, UV		✓	✓	✓	No TL83	✓	No CWF
Standard Light Sources 220V models: D65, TL84, A, TL83, UV		✓	✓	✓	No TL83	✓	No TL83
Possible substitution of TL83 with: D50, D75, Horizon or U35	✓	✓	✓	✓		✓	
Optional: LED Source 3000, 3500, or 4000K	✓	✓	✓	✓	✓	✓	✓
Possible substitution of CWF/TL84 with: D50	✓	✓	✓	✓	✓	✓	✓
<b>Viewing area (h x w x d):</b>		<b>48cmx71cmx51cm 19"x28"x20"</b>	<b>64x102x64cm 25"x40"x25"</b>	<b>76x132x76cm 30" x 52" x 30"</b>	<b>36x61x34cm 14"x24"x13"</b>	<b>36x61x40cm 14"x24"x16"</b>	<b>36x61x40cm 14"x24"x16"</b>
Units can be coupled for larger width	✓	✓	✓	✓			
<b>Physical dimensions (h x w x d):</b>	<b>13x102x66cm</b>	<b>63x76x55cm 24.75"x30"x21.5"</b>	<b>79x107x68cm 31"x42"x26.75"</b>	<b>91x137x80cm 36"x54"x31.5"</b>	<b>48x67x42cm 19"x26.5"x16.5"</b>	<b>48x67x48cm 19"x26.5"x19"</b>	<b>48x67x48cm 19"x26.5"x19"</b>
<b>Shipping Weight</b>	<b>16kg/35lbs</b>	<b>32kg/70lbs</b>	<b>64kg/140lbs</b>	<b>93kg/205lbs</b>	<b>14kg/30lbs</b>	<b>17kg/38lbs</b>	<b>17kg/38lbs</b>
Compliant to ASTM d1729	✓	✓	✓	✓	✓	✓	✓
Compliant to SAE J361, Tappi 7513, BS-950/2, AS 1580.6001.1	✓	✓	✓	✓	✓	✓	✓